



## **WATER OUTLET RESTRICTOR KIT P/N 8229**

**FITS G.M. V8, G.M. V6, & SMALL BLOCK FORD ENGINES**

These plates restrict the coolant flow leaving the engine block on its way back to the radiator. The three sizes of restrictor plate holes (5/8", 3/4", & 1" diameter) allow you to control the water temperature to the engine builder's specifications. You control this by permitting the water to remain in the radiator longer for better heat dissipation and cooling before it returns to the water pump and engine block.

**W524**

**Revision Date: 9-14-12**



## **WATER OUTLET RESTRICTOR KIT P/N 8229**

**FITS G.M. V8, G.M. V6, & SMALL BLOCK FORD ENGINES**

These plates restrict the coolant flow leaving the engine block on its way back to the radiator. The three sizes of restrictor plate holes (5/8", 3/4", & 1" diameter) allow you to control the water temperature to the engine builder's specifications. You control this by permitting the water to remain in the radiator longer for better heat dissipation and cooling before it returns to the water pump and engine block.

**W524**

**Revision Date: 9-14-12**



## **WATER OUTLET RESTRICTOR KIT P/N 8229**

**FITS G.M. V8, G.M. V6, & SMALL BLOCK FORD ENGINES**

These plates restrict the coolant flow leaving the engine block on its way back to the radiator. The three sizes of restrictor plate holes (5/8", 3/4", & 1" diameter) allow you to control the water temperature to the engine builder's specifications. You control this by permitting the water to remain in the radiator longer for better heat dissipation and cooling before it returns to the water pump and engine block.

**W524**

**Revision Date: 9-14-12**



## **WATER OUTLET RESTRICTOR KIT P/N 8229**

**FITS G.M. V8, G.M. V6, & SMALL BLOCK FORD ENGINES**

These plates restrict the coolant flow leaving the engine block on its way back to the radiator. The three sizes of restrictor plate holes (5/8", 3/4", & 1" diameter) allow you to control the water temperature to the engine builder's specifications. You control this by permitting the water to remain in the radiator longer for better heat dissipation and cooling before it returns to the water pump and engine block.

**W524**

**Revision Date: 9-14-12**