

## Installation Instructions CAST ALUMINUM DIFFERENTIAL COVER for AAM 11.5"

Fits most 2001-11 GM 2500/3500 & 2003-13 Ram 2500/3500. For specific vehicles see "Applications" tab on this product's webpage.

**Part No. 11317**

Rev. 1/8/2020

### INTRODUCTION

This rear end cover can be installed in about an hour by carefully following the instructions. It is suggested that the vehicle be allowed to cool off for a few hours to avoid burns from hot oil and parts. The vehicle should be off the ground for ease of installation -jack stands, wheel ramps or a hoist will work fine. **CAUTION: MAKE SURE VEHICLE IS FIRMLY SUPPORTED -DO NOT WORK UNDER A VEHICLE IF IT IS SUPPORTED BY ONLY A JACK!**

**WORK SAFELY!** For maximum safety, perform this installation on a clean, level surface and with the engine turned off. Place blocks or wedges in front of and behind both rear wheels to prevent movement in either direction.

### IMPORTANT!

Visually confirm that you have the proper cover for your specific application before you begin. Compare the bolt count, shape and general size. The AAM 11.5" axle, also known as the GM 11.5" axle replaced the GM 10.5" 14 Bolt in many Chevy and GMC full size trucks in 2001. It is also used by Chrysler under many of their heavy duty Dodge Ram 2500 and 3500 series trucks. Refer to the figure at the right for visual identification of the AAM 11.5" rear differential.



### INSTALLATION

1. Clean axle housing cover area from dirt and other debris.

**NOTE: On some vehicles it might be necessary to remove some parts (e.g. sway bar, pan hard rod) to make the installation of the cover easier.**

2. Place a drain pan underneath the axle housing.

3. Remove the axle housing drain plug with a 3/8" square ratchet and extension (See Figure 1).



4. Remove all the bolts except one at the top. Loosen the remaining bolt but do not remove.

5. Carefully pry the cover loose with a flat head screw driver, being careful not to damage the surface, and allow any remaining oil to drain.


6. Remove the last bolt and the cover once completely drained.

7. Using a dry lint free rag, clean the accessible areas of the axle housing and check internal components for visible excessive wear or other problems.




8. Using a razor blade or gasket scraper, clean all gasket material from the axle housing surface (See Figure 2).


9. We recommend running a tap through each threaded cover hole on the axle housing to ensure an accurate torque on all bolts.



10. Install the supplied load bolts in each boss from the inside of the B&M Differential Cover until they bottom out (See Figure 3 & 4).



11. Apply a bead of RTV silicone gasket maker to the B&M Differential Cover. Run the bead inside the bolt holes (See Figure 4).



12. Install the B&M Differential Cover on the axle housing using a supplied bolt and washer at a bottom hole on the cover so it can be used as a guide.

13. Install the rest of the supplied bolts and washers and torque to 15ft/lbs. in a crisscross pattern.


14. Screw in the two load bolts by hand until they touch the bearing caps. Torque the load bolts to 5ft.lbs. max.

**NOTE: Do not over torque the load bolts as you run the risk of distorting the bearing caps, creating abnormal wear and premature failure.**

15. Apply a very small amount of RTV on the threads of the load bolts and install on the two supplied jam nuts on the load bolts. Torque the jam nuts to 5ft/lbs.

16. Install the supplied magnetic 1/4" NPTF drain plug on the B&M Differential Cover and tighten (See Figure5).

17. Fill with factory recommended gear oil using the B&M Differential Cover fill plug hole. Add gear oil until oil runs out of the **axle housing fill level hole**. (Not the Fill Hole on the cover)



18. Install the axle housing fill plug and torque to 20ft/lbs.

19. Install the supplied 1/2"NPT fill plug on the B&M Differential Cover and tighten.

20. Install and tighten any other parts (e.g., sway bar, pan hard rod) if removed.

### Tools List

Jack & Jack Stands  
Drain Pan  
Rags  
RTV Silicone Gasket Maker  
Gear Oil  
Gear Oil Pump  
Torque Wrenches  
3/8" Ratchet & 3" Extension  
1/4" Allen  
3/8" Allen  
3/4" Socket  
Flat Blade Screwdriver

### Parts List

(1) Cast Aluminum Cover  
(2) Load Bolts  
(2) Jam Nuts  
(1) 1/4" NPTF Drain Plug  
(1) 1/2" NPT Filler Plug  
(14) M8-1.25 x 25MM Bolt  
(14) 5/16" Washers

**IMPORTANT: RETAIN THESE INSTRUCTIONS FOR FUTURE REFERENCE**

