



## GMBRKT3-BEL

50-inch Straight LED Light Bar Upper Windshield for Chevy  
2007-2013 Avalanche/Silverado 1500, 2007-2014 Silverado  
2500/3500, 2007-2013 Suburban/Tahoe 1500, GMC 2007-2013  
Sierra 1500, 2007-2014 Sierra 2500/3500, 2007-2013 Yukon/  
Yukon XL 1500

## Parts:

1 - Driver Side Bracket  
1 - Passenger Side Bracket  
2 - Rubber Spacer Pads  
6 - 5/16" x 1" Button-head Screws  
6 - Nut Inserts  
6 - 5/16"x1" Bolts, Washers and 3/8" Nuts

## PRE-INSTALLATION

**Professional installation by a certified technician is strongly recommended.**

*Not responsible for altered products. No claims are made regarding any after-market devices. Any and all claims implied in this document excluded.*

### NOTES:

Light bar not included in kit.

### REQUIRED TOOLS:

1/2" Wrench	9/16" Wrench	3/16" Allen Wrench	6mm Allen Wrench	Center Drill
33/64" Drill Bit	Tape Measure	Masking Tape	Permanent Marker	

## INSTALLATION INSTRUCTIONS

**STEP 1:** Disconnect positive battery lead before installation.

**STEP 2:** Open doors and pull back weather stripping above windshield on both sides.

**STEP 3:** Apply masking tape to painted surface so brackets will not scratch paint.

**STEP 4:** Install brackets on 50" light bar (not included). Use hardware supplied with kit and hand tighten.

**STEP 5:** Place brackets on top of door frame 1/2" above windshield. Mark mounting holes with marker or punch (3 per side).

**STEP 6:** Remove brackets from vehicle. Drill holes with center drill or 1/4" drill bit.

**STEP 7:** Drill holes out to 33/64" (.515") diameter.

**STEP 8:** Assemble nut inserts. Place washer on 5/16" x 1" bolt, then thread on 3/8" nut. Thread bolt (with nut and washer) into nut insert. Place assembly into hole in door frame.

**STEP 9:** Hold nut in place with 9/16" wrench and tighten bolt with 1/2" wrench to compress insert and hold it in place.

**STEP 10:** Repeat for all six nut inserts.

**STEP 11:** Place rubber spacer pad on inside of each bracket.

**STEP 12:** Remove masking tape.

**STEP 13:** Hold light bar and brackets in place and line up mounting holes. Secure with included 5/16" x 1" button-head screws. Tighten with 3/16" allen wrench.

**STEP 14:** Tighten light bar mount screws on each side with 6mm allen wrench.

**STEP 15:** Wire power to light bar per instructions supplied with kit.

**STEP 16:** Reinstall factory rubber door seal.

**STEP 17:** Reconnect positive battery lead.

## POST-INSTALLATION

**MAINTENANCE:** Periodically check to ensure that all fasteners are properly tightened.