



Installation Instructions

Part Nos. 5000023; 5000025; and 5000028

Shifter Cable

For Hurst Quarter Stick®, Quarter Stick 2, Pistol Grip, Auto Stick 3, Dual Gate 2, and Lightning Rod shifters

Rev 02/27/2020

WORK SAFELY! For maximum safety, perform this installation on a clean, level surface and with the engine turned off. Place blocks or wedges in front of and behind both rear wheels to prevent movement in either direction.

CAUTION: To avoid any possibility of bodily injury or damage to vehicle, do not attempt installation until you are confident that the vehicle is safely secured and will not move.

1. Insert the shifter cable into the mounting bracket and secure using a clip. Push the clip onto the cable inside of the bracket with the tab facing rearward and tap in until fully seated.

NOTE: It may be necessary to make a fine adjustment of the cable pivot before the shifter will engage completely.

2. Install the cable pivot onto the threaded end of the shifter cable. Adjust the pivot end of the cable until it moves freely in and out of the hole in the transmission selector lever. Lock the adjustment by tightening the jam nut against the cable pivot. Then insert the pivot in the selector lever and secure using the cotter pin.

IMPORTANT: RETAIN THESE INSTRUCTIONS FOR FUTURE REFERENCE

Technical Service

Hurst Performance maintains a highly trained technical service department to answer your technical questions, provide additional product information and offer various recommendations.



Hurst Performance Products

(866) 464-6553

www.hurst-shifters.com