



Detroit Speed
Detroit Speed Stainless Steel Headers
DSE Hydroformed Subframe w/LS Engine
P/N: 061001DS

The Detroit Speed headers are designed and engineered for LS engines installed in the Detroit Speed Hydroformed Subframe when installed in a 1967-1974 Camaro/Firebird or a 1968-1974 Nova. These headers are designed for performance, maximum ground clearance, and a clean engine compartment appearance. The DSE Stainless Steel LS headers are durable, attractive, and come with the necessary clamps to make installation easy. The DSE Stainless Steel LS Headers use a 1 - 7/8" primary tube diameter with 4-way merge collectors featuring V-Band clamps. Each header features an O₂ sensor bung in the collector.



NOTE: When installing these headers in the DSE Hydroformed Subframe, it is required that you use the DSE LS Engine Mount Kit P/N: 060404DS.

Recommended Parts for Installation		
Description	Manufacturer	Part Number
Header Gasket	SCE Gaskets	4119
	GM LS Gaskets	12617944
Header Studs	ARP	434-1301

If an O₂ sensor is not being used, the bung can be plugged using a M18 x 1.75 plug.

If you have any questions before or during the installation of this product, please contact Detroit Speed at tech@detroitsspeed.com or 704.662.3272

Legal Disclaimer: Detroit Speed is not liable for personal, property, legal, or financial damages from the use or misuse of any product we sell. The purchaser is solely responsible for the safety and performance of these products. No warranty is expressed or implied.